

# GAMING READER



## MAGNETIC PARTIAL INSERT READER

### KEY FEATURES:

- Supports single, dual, or triple track magnetic heads
- Stainless steel roller design reduces card scratching
- Vandal resistant bezel, chassis & read-head
- Proprietary design removes ESD from card surface
- Bezel options compatible with industry-standard mounting options
- Capability of lengthening insertion depth - 2 options
- Large debris slot for jam-proof operation



# GAMING READER SPECS

<b>DIMENSIONS</b>	88.66mm (W) x 60mm (D) x 25.4mm (H)
<b>INTERFACE</b>	RS232, TTL, USB
<b>OPERATING LIFE</b>	1,000,000 Cycles (Minimum)
<b>OPERATING TEMPERATURE</b>	0°C to 60°C
<b>POWER</b>	RS232 35m Max. USB +5 DC TTL Standby Mode: 100µA Max Operating Mode: 3mA Max
<b>SHOCK</b>	Sweep 10Hz to 50Hz/min; 294 m/s <sup>2</sup> (30G)
<b>STORAGE TEMPERATURE</b>	-40°C to 60°C
<b>SWIPE SPEED</b>	3 to 60 Inches per Second, Bi-Directional
<b>WARRANTY</b>	One Year, Parts & Labor
<b>WEIGHT</b>	136g (.30 lbs)



## CORPORATE HEADQUARTERS

10721 WALKER STREET  
CYPRESS, CA 90630  
T: (714) 761-6368  
TF: (800) 984-1010  
F: (714) 761-8880  
SALES@IDTECHPRODUCTS.COM

## ASIA

+886-3-326-5988 (TAIWAN)  
ASIA@IDTECHPRODUCTS.COM

## LATIN AMERICA

(714) 761-6368  
SALES@IDTECHPRODUCTS.COM

## EUROPE, MIDDLE EAST & AFRICA

EMEA@IDTECHPRODUCTS.COM

ISO 9001 CERTIFIED  
ISO 14001 CERTIFIED

# IDTECH®

Value through Innovation

IDTECHPRODUCTS.COM

