



OMNI

SLOT READER FOR BARCODE AND MAGSTRIPES

The Omni reads up to 3 tracks of information with a single swipe in either direction. In combination, the same Omni unit can read both barcode and MagStripe media. It scans barcodes printed on paper, card stock, or plastic. An infrared option is available for security-based applications, where barcodes are over-printed to prevent duplication. The Omni reader is designed for demanding applications, such as for access control or in self-service kiosks. Weatherproof, sealed, or extended temperature versions are available for use in harsh environments.



OMNI SPECS

INTERFACE	TTL (TTL barcode and/or magnetics clock and data), keyboard wedge, Standard SIA 26-bit Wiegand, RS232, USB-KB, USB-RS232
POWER	+5 VDC +/-10%, 35mA/30mA maximum
OPERATING TEMPS	32° F to 131° F (0° C to 55° C)
STORAGE TEMPS	-31° F to 158° F (-35° C to 70° C)
HUMIDITY	Maximum 95% non-condensing, dry storage
WARRANTY	One Years, parts and labor
WEIGHT	1.4 lb. (including power pack)
CABLE LENGTH	6-foot straight cable
DIMENSIONS	5 inches (127 mm) x 2.05 inches (52 mm) x 1.38 inches (35 mm)
CABLE CONNECTOR	TTL- 9 pin squeeze, Keyboard - 6 pin mini DIN, RS232 - DE9F, TTL Mag/Bar Code Combo Readers-stripped and

CONTACT US TODAY!

CORPORATE HEADQUARTERS
10721 WALKER STREET
CYPRESS, CA 90630
TEL: (714) 761-6368
TF: (800) 984-1010
SALES@IDTECHPRODUCTS.COM

ASIA
+886-3-326-5988 (TAIWAN)
ASIA@IDTECHPRODUCTS.COM

LATIN AMERICA
(714) 761-6368
SALES@IDTECHPRODUCTS.COM

EUROPE, MIDDLE EAST & AFRICA
EMEA@IDTECHPRODUCTS.COM

ISO 9001 CERTIFIED

