

SMARTPIN L80

COMPACT PCI PTS 6.X PIN PAD

The SmartPIN L80 is designed for unattended solutions where encrypted Chip & PIN entry is required and is available with or without LCD. The compact footprint allows for PIN Entry and enables Chip & PIN transactions when paired with VP5300 or VP5300M. The whole solution is perfect for kiosks and unattended solutions requiring chip card support. Examples of usage are Fuel Dispensers, Ticket Vending Machines, Parking Kiosks and various other unattended verticals.



with LCD

without LCD

FEATURES

- Compact Footprint
- PCI PTS 6.X
- User Friendly Tactile Keys
- Extensive Temperature Range
- Slick and Modern design for Durability
- Low Power Consumption
- DUKPT Key Management
- AES & TDES Encryption (Supports online and offline PIN)
- EMV Contact and Contactless support when connected with VP5300/VP5300M
- Easy plug and play with ID TECH readers
- 100% compatible with other ID TECH PIN Pads (L100)

CONTACT US TODAY!

CORPORATE HEADQUARTERS

10721 WALKER STREET
CYPRESS, CA 90630
TEL: (714) 761-6368
TF: (800) 984-1010
SALES@IDTECHPRODUCTS.COM

ASIA

+886-3-326-5988 (TAIWAN)
ASIA@IDTECHPRODUCTS.COM

LATIN AMERICA

(714) 761-6368
SALES@IDTECHPRODUCTS.COM

EUROPE, MIDDLE EAST & AFRICA

EMEA@IDTECHPRODUCTS.COM

SMARTPIN L80 SPECS

INTERFACE	RS232 & USB
POWER	5VDC; Power consumption: <200mA
OPERATING TEMPS	-20°C to 70°C
STORAGE TEMPS	-40°C to 80 °C
HUMIDITY	15% to 95%, non-condensing
KEY DURABILITY	Minimum 1,000,000 key presses
MTBF	120,000 power-on hours calculated
ESD IMMUNITY	±6kV contact, and ±10kV air discharge to exposed surfaces
APPROVALS	PCI PTS 6.X; CE; FCC; REACH; RoHS; VCCI
WARRANTY	One year, parts and labor
DIMENSIONS	93.5mm (W) x 60mm (L) x 26.4mm (D)
KEYS	Numeric (10), Operation (2), and Function (3)
DISPLAY	128 x 32 pixels
IMPACT PROTECTION	IK 08
INGRESS PROTECTION	IP 65

ISO 9001 CERTIFIED
ISO 14001 CERTIFIED

