

SECURE & EASY PAYMENT INTEGRATION

ATMs, kiosks, parking, transit, vending whatever your self-service environment entails, we've got you covered, with the latest in PCI certified contact EMV and contactless payment technology. ID TECH's family of unattended solutions allows users secure and easy integration of cashless payments, while providing a simple consumer experience through an easy-to-use interface.







10721 Walker Street Cypress, CA 90630

(714) 761-6368 ales@idtechproducts.com



VP5300 BUNDLE FEATURES

All Payment Options

The VP5300 Bundle solution consists of a PCI-certified hybrid insert reader, PCI-certified PIN pad, and NFC contactless antenna allowing customers to use all popular cashless payment options.

Flexible Communications and Connectivity

Our products provide a wide range of integrated connectivity to communicate with kiosks, acquirer hosts, including USB-HID and RS232, and Ethernet.

Contactless Acceptance

The VP5300 is compatible with ISO14443, Mifare, and ISO 18092 Peer-to-Peer. The Unattended Bundle supports loyalty programs, EMV payments, and NFC payments. Additionally, the VP5300 supports latest contactless ticketing functionality found in most transit systems worldwide.

Rugged and Tamper Resistant

All three bundled products are designed to withstand the rigors of outdoor environments and meet a high IK impact rating and IP65 protection from dust, liquid, and other harmful substances.

Eco-Friendly

These readers are perfect for solar powered kiosks because they have a low power stand-by mode and stop mode, providing optimal energy consumption. ID TECH's commitment to excellence includes our commitment to the environment as well as our commitment to quality.

Highest Encryption Security

The VP5300 Bundle provides the highest PCI PTS methods including TDES, AES, and RSA.

		VP5300 NFC ANTENNA	VP5300	SMARTPIN L100	SMARTPIN L80
SAM					
Card Readers	Magstripe		\checkmark		
	Contactless EMV	\checkmark			
	Contact / EMV		\checkmark		
LCD Display				\checkmark	\checkmark
Keyboard	Number of Keys			19	15
	Key Texture			ADA Compliant	ADA Compliant
Beeper / LEDs		Based on EMV Specs	LED, Beeper	Beeper, Status LED	Beeper, Status LED
Connections		Connects to VP5300	RS232, USB, Ethernet	Connects to VP5300	Connects to VP5300
Power Supply		Powered by VP5300	External Power Supply 9V to 12V	Powered by VP5300	Powered by VP5300
Size (mm)	WxLxD	55 x 65 x 14.5 mm	103 x 136.5 x 73 mm	107.5 x 140 x 27.9 mm	93.5 x 60 x 26.4 mm
Weight (kg)		0.056 kg	0.695 kg	0.53 kg	0.111 kg
Environment	Operating Temperature	-25°C to 70°C	-25°C to 65°C	-25°C to 70°C	-20°C to 70°C
	Storage Temperature	-40°C to 80°C	-40°C to 80°C	-30°C to 80°C	-40°C to 80°C
IP	Ingress Protection	IP65	IP65	IP65	IP65
к	Impact Protection	IK10	IK10	IK09	IKO8
PCI PTS		5.X	5.X	4.X	6.X
SRED		\checkmark	\checkmark	\checkmark	\checkmark



CORPORATE HEADQUARTERS 10721 WALKER STREET

TEL: (714) 761-6368 TF: (800) 984-1010 SALES@IDTECHPRODUCTS.COM

ASIA

+886-3-326-5988 (TAIWAN) ASIA@IDTECHPRODUCTS.COM

LATIN AMERICA (714) 761-6368

EUROPE, MIDDLE EAST & AFRICA EMEA@IDTECHPRODUCTS.COM

SALES@IDTECHPRODUCTS.COM

ISO 9001 CERTIFIED ISO 14001 CERTIFIED

