



OMNI

Slot Reader for Barcodes and/or MagStripes

The Omni reads up to 3 tracks of information with a single swipe in either direction. In combination, the same Omni unit can read both barcode and MagStripe media. It scans barcodes printed on paper, card stock, or plastic. An infrared option is available for security-based applications, where barcodes are over-printed to prevent duplication. The Omni reader is designed for demanding applications, such as for access control or in self-service kiosks. Weatherproof, sealed, or extended temperature versions are available for use in harsh environments.



OMNISPECS

CONTACT US TODAY!

CORPORATE HEADQUARTERS

10721 WALKER STREET
CYPRESS, CA 90630
TEL: (714) 761-6368
TF: (800) 984-1010
FAX: (714) 761-8880
SALES@IDTECHPRODUCTS.COM

ASIA

+886-3-326-5988 (TAIWAN)
ASIA@IDTECHPRODUCTS.COM

CANADA

(714) 761-6368
CANADA@IDTECHPRODUCTS.COM

SOUTH AMERICA

+55-11-3079-2255
INTERNATIONSALES@
IDTECHPRODUCTS.COM

EUROPE, MIDDLE EAST & AFRICA

EMEA@IDTECHPRODUCTS.COM

INTERFACE

TTL (TTL barcode and/or magnetics clock and data),
keyboard wedge, Standard SIA 26-bit Wiegand, RS232,
USB-KB, USB-RS232

oc' 7q

+5 VDC +/-10%, 35mA/30mA maximum

OPERATING TEMPS

32° F to 131° F (0° C to 55° C)

STORAGE TEMPS

-31° F to 158° F (-35° C to 70° C)

HUMIDITY

Maximum 95% non-condensing, dry storage

' ! qq! ^{—

c⁻ — — § - §⁻ - ®

WEIGHT

1.4 lb. (including power pack)

CABLE LENGTH

6-foot straight cable

DIMENSIONS

5 inches (127 mm) x 2.05 inches (52 mm) x 1.38 inches
(35 mm)

CABLE CONNECTOR

TTL- 9 pin squeeze, Keyboard - 6 pin mini DIN, RS232 -
DE9F, TTL Mag/Bar Code Combo Readers-stripped and

ISO 9001 CERTIFIED

