

2D SCAN FX200



MULTI-PURPOSE FIXED MOUNT 2D BARCODE READER

KEY FEATURES:



- Plug-and-play integration
- 60 frames per second
- Various scan modes including:
 - Continuous Mode
 - Level Mode
 - Pulse Mode
 - Sense Mode
- 1GHz X1500 processor
- Reads multiple global symbologies
- Flexible & compact



2D SCAN FX200 SPECS

2D	AZTEC, Code One, CSC, Data Matrix, GM, Maxicode, Micro PDF417, Micro QR, PDF417, QR Code, Etc.
DIMENSIONS	41.5mm (W) x 49.5mm (D) x 24.3mm (H)
DROP TEST	1.5m
HUMIDITY	5% to 95% (non-condensing)
IMAGE SENSOR	CMOS 1280*800
INDICATORS	Beep Tone, LED
INTERFACES	USB (IDBB-6642LRB)
POWER REQUIREMENTS	DC 5V±5%
PROCESSOR	1GHz, X1500
SCAN MODE	Continuous, Level, Pulse & Sense Modes
SCAN RATE	60 Frames per Second
TEMPERATURES	-20°C to 60°C (Operating Temperature) -40°C to 70°C (Storage Temperature)
WEIGHT	75g



CORPORATE HEADQUARTERS

10721 WALKER STREET
CYPRESS, CA 90630
T: (714) 761-6368
TF: (800) 984-1010
F: (714) 761-8880
SALES@IDTECHPRODUCTS.COM

ASIA

+886-3-326-5988 (TAIWAN)
ASIA@IDTECHPRODUCTS.COM

LATIN AMERICA

(714) 761-6368
SALES@IDTECHPRODUCTS.COM

EUROPE, MIDDLE EAST & AFRICA

EMEA@IDTECHPRODUCTS.COM

ISO 9001 CERTIFIED
ISO 14001 CERTIFIED

IDTECH®

Value through Innovation

IDTECHPRODUCTS.COM

