



KIOSK V

STANDALONE CONTACTLESS PERIPHERAL

KEY FEATURES:



- PCI PTS 6.X certified (SRED version only)
- Contactless EMV L1 & L2 certified
- Supports Apple VAS & Google Smart Tap, Mifare Suite & FeliCa
- Supports the latest Visa, Mastercard, American Express & Discover L2 kernels & extensive international kernels
- Supports major transit kernels like Visa, American Express, Discover & Interac Transit
- Supports direct & remote key injection
- Ruggedized, water resistant product made for indoor & outdoor use

ONE COMMON KERNEL. ONE INTEGRATION. MULTIPLE ENVIRONMENTS.



KIOSK V SPECS

ELECTRICAL	CONNECTIVITY	BLE (Optional), RS232, TTL & USB
	ENCRYPTION	AES, RSA, TDES & Transarmor
	KEY MANAGEMENT	DUKPT
	MTBF	500,000 Hours
	POWER	5V via USB
ENVIRONMENTAL	IMPACT RATING	IK08
	INGRESS PROTECTION RATING	IP65
	OPERATING HUMIDITY	Maximum 95% (Non-Condensing)
	OPERATING TEMPERATURE	-30°C to 70°C (Max Change of 10°C per Hour)
	STORAGE TEMPERATURE (SRED)	-30°C to 85°C (Non-Condensing)
	STORAGE TEMPERATURE (NON-SRED)	-40°C to 85°C (Non-Condensing)
MECHANICAL	DIMENSIONS	75 mm (H) x 60 mm (W) x 11.2 mm (D)
	MEMORY	Flash 16 MB (External Flash Size is 16 MB)
	WEIGHT	1.76 oz



CORPORATE HEADQUARTERS

10721 WALKER STREET
 CYPRESS, CA 90630
 T: (714) 761-6368
 TF: (800) 984-1010
 F: (714) 761-8880
 SALES@IDTECHPRODUCTS.COM

ASIA

+886-3-326-5988 (TAIWAN)
 ASIA@IDTECHPRODUCTS.COM

LATIN AMERICA

(714) 761-6368
 SALES@IDTECHPRODUCTS.COM

EUROPE, MIDDLE EAST & AFRICA

EMEA@IDTECHPRODUCTS.COM

ISO 9001 CERTIFIED
 ISO 14001 CERTIFIED

IDTECH®

Value through Innovation

IDTECHPRODUCTS.COM

