

GAMING READER



MAGNETIC PARTIAL INSERT READER

KEY FEATURES:

- Supports single, dual, or triple track magnetic heads
- Stainless steel roller design reduces card scratching
- Vandal resistant bezel, chassis & read-head
- Proprietary design removes ESD from card surface
- Bezel options compatible with industry-standard mounting options
- Capability of lengthening insertion depth - 2 options
- Large debris slot for jam-proof operation



GAMING READER SPECS

ELECTRICAL	CONNECTIVITY	RS232, TTL, USB
	POWER REQUIREMENTS	RS232 35 m Max. USB +5 DC TTL Standby Mode: 100µA Max Operating Mode: 3mA Max
	SHOCK	Sweep 10 Hz to 50 Hz/min; 294 m/s ² (30G)
	SWIPE SPEED	3 to 60 Inches per Second; Bi-Directional
ENVIRONMENTAL	OPERATING TEMPERATURE	0°C to 60°C
	STORAGE TEMPERATURE	-40°C to 60°C
MECHANICAL	DIMENSIONS	88.66 mm (W) x 60 mm (D) x 25.4 mm (H)
	OPERATING LIFE	1,000,000 Cycles (Minimum)
	WARRANTY	One Year, Parts & Labor
	WEIGHT	4.8 oz



CORPORATE HEADQUARTERS

10721 WALKER STREET
CYPRESS, CA 90630
T: (714) 761-6368
TF: (800) 984-1010
F: (714) 761-8880
SALES@IDTECHPRODUCTS.COM

ASIA

+886-3-326-5988 (TAIWAN)
ASIA@IDTECHPRODUCTS.COM

LATIN AMERICA

(714) 761-6368
SALES@IDTECHPRODUCTS.COM

EUROPE, MIDDLE EAST & AFRICA

EMEA@IDTECHPRODUCTS.COM

ISO 9001 CERTIFIED
ISO 14001 CERTIFIED

IDTECH®

Value through Innovation

IDTECHPRODUCTS.COM

