



AP3880P

ANDROID-BASED MOBILE POS with 5.5" SCREEN & PRINTER

KEY FEATURES:

- Support multiple payment methods including QR/barcodes, NFC, magstripe & IC cards
- Features a compact, high-voltage thermal printer with printing speed of 100mm/s
- Slim form factor with 2.5mm bezel & 5.5" LCD touchscreen
- High performance processing & advanced connectivity

OPTIONAL CHARGING CRADLE:

- Compact footprint fits any type of payment environment



CERTIFICATIONS:

-PCI PTS 6.1
-EMV Contact L1 & L2
-EMV Contactless L1
-AMEX
-Discover
-Mastercard
-Visa VCPS

-Interac
-JCB MIR
-UPI
-eftpos (on the roadmap)
-Rupay (on the roadmap)

-Felica
-Mifare
-Apple Pay
-Apple VAS ECP 1.0
-Google Smart Tap
-Samsung Pay

-CE
-FCC
-IC
-MasterCard TQM
-NCC
-REACH
-ROHS
-Weee



AP3880P SPECS

OPERATING SYSTEM	Android 11	ADAPTER	Input: AC 100-240V, 50/60Hz Output: 5V/2A
PROCESSOR	Quad Cortex-A53, 2.0GHz	SPEAKER	1W
DISPLAY	5.5 Inch IPS Screen, 1280 x 720 HD Capacitive; Multi-Point Touch Panel	BUTTON	Power Button / Scan Button
PRINTER	2" High Thermal Printer Print Speed: 100mm/s Roll Size: 58*40mm	CONNECTIVITY	BLE 5.0, Dual Band WiFi-2.4G/5G, IEEE802.11 a/b/g/n/ac, LTE-2G/3G/4G
CAMERA	Rear Camera: 5M AF		
DIMENSIONS	209.09 mm (L) x 78.59 mm (W) x 19 mm (H)	ENCRYPTION	TEDS 112 , AES 128 TransArmor TDES, TransArmor AES, Salted Hash, DKI, RKI
WEIGHT	443g		
BATTERY	Removable Lithium Polymer; 7.4V/2620mAh		
MEMORY	2GB LPDDR4 + 32GB eMMC	ACCESSORIES	Cradle Multi-Port Cradle
PERIPHERAL PORTS	Type C USB2.0 OTG 5*Pogo Pin	OPERATING TEMPERATURE	0°C to 50°C
CARD SLOT	(2) Micro SIM, (2) PSAM, (1) T-Flash up to 128GB.	STORAGE TEMPERATURE	-20°C to 60°C



IDTECH®

Value through Innovation

IDTECHPRODUCTS.COM



CORPORATE HEADQUARTERS

10721 WALKER STREET
CYPRESS, CA 90630
T: (714) 761-6368
TF: (800) 984-1010
F: (714) 761-8880
SALES@IDTECHPRODUCTS.COM

ASIA

+886-3-326-5988 (TAIWAN)
ASIA@IDTECHPRODUCTS.COM

LATIN AMERICA

(714) 761-6368
SALES@IDTECHPRODUCTS.COM

EUROPE, MIDDLE EAST & AFRICA

EMEA@IDTECHPRODUCTS.COM

ISO 9001 CERTIFIED
ISO 14001 CERTIFIED